

SKID MOUNTED SHEAR



DESCRIPTION

Flowline Specialists' shears are scrap product processing units mounted on skids. It is primarily used for decommissioning umbilicals, cables, pipes and flexibles. Product is fed into the shear using a tensioner or LCE. The shear is supplied with a hydraulically powered base allowing it to move forward, cut the product and retract, leaving the product in easily transportable sections.

The shear is hydraulically powered and operated using a control valve. All units are supplied with dedicated rigging suitable for offshore use.

SPECIFICATIONS

	FLO-DS01 Dudley	FLO-DS02 Dudley	FLO-BS01 La Bounty
Length	3,500mm	3,500mm	3,500mm
Width	1,814mm	1,844mm	1,844mm
Height	2,050mm	2,400mm	2,025mm
Jaw opening	600mm	700mm	711mm
Jaw depth	760mm	800mm	737mm
Shear force	800Te	1,250Te	1,140Te
Shear weight	6,500kg	6,000kg	9,000kg

Contact us

UK Division: +44 (0) 1651 871 872 • info@flowlinespecialists.com

Dubai - UAE Division: +971 56 835 7671 • uae@flowlinespecialists.com

Operational bases in Norway and The Netherlands

www.flowlinespecialists.com

FLO-SH-DS-01 Rev 00